

HAZARDOUS SUBSTANCES RISK ASSESSMENT

Designer Contracts Ltd

Unit 8, Church View, Coney Green, Chesterfield, S45 9HA

CPL Super Flow 30 Liquid	Date of Assessment : 12/12/2022	Reference : CPL - Tilemaster Super Flow 30 Liquid
Risk Assessor : Laura Cross	Risk Assessor :	
Other People Involved in Making This Assessment : Antony Maidens		

R or H Descriptors:	S or P Descriptors:
Additional Information	
Workspace Exposure Limit (WEL) No WEL stated on Safety Data Sheet	

Primary route(s) of entry : Absorption, Ingestion, Inhalation	
This is a Group Substance.	The quantity used per batch or work period is: Medium (1-1000kg or 1-1000L)
The Substance is a Liquid of Low volatility	
is the control measure appropriate to control the health risks from the use of this substance. Health Surveillance is not required.	

Existing Control Measures
1. Always use in well ventilated areas avoid contact with skin and eyes.
2. First Aid Measures: Inhalation, May cause irritation to mucous membranes. Move the exposed person to fresh air. Seek medical attention if irritation or symptoms persist.
3. Eye contact: May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
4. Skin Contact: May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
5. Ingestion: May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.
6. Do not allow runoff water to enter sewers or drains. Stable under normal conditions.
7. Do not allow product to enter drains. Prevent further spillage if safe.
8. Methods and material for containment and cleaning up: Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
9. Conditions for safe storage: Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers. Protect from frost.
10. Wear protective clothing, safety goggles and chemical resistant gloves.

11. Disposal of packaging This material and its container must be disposed of in a safe way. EWC code 08 04 09 * Always return empty packaging to region and dispose of in Drum A

Documents Associated with this Risk Assessment : Tilemaster Super Flow 30 Latex SDS.pdf(Safety Data Sheet) Superflow 30 Health (SDS)

Review Date : 23/12/2023