

HAZARDOUS SUBSTANCES RISK ASSESSMENT

Designer Contracts Ltd

Unit 8, Church View, Coney Green, Chesterfield, S45 9HA

CPL Super Flow 30 Powder	Date of Assessment : 12/12/2022	Reference : CPL - Super Flow 30 Powder
Risk Assessor : Laura Cross	Risk Assessor :	
Other People Involved in Making This Assessment : Antony Maidens		

R or H Descriptors:	S or P Descriptors:
Additional Information	
Workspace Exposure Limit (WEL) long term 8hr mg/m3 short term 15 min mg/m3	

Primary route(s) of entry : Absorption, Ingestion, Inhalation	
This is a Group Substance.	The quantity used per batch or work period is: Medium (1-1000kg or 1-1000L)
The Substance is a Solid of Low dustiness	
is the control measure appropriate to control the health risks from the use of this substance. Health Surveillance is not required.	

Existing Control Measures
1. Always use in a well ventilated area.
2. First Aid Measures: Inhalation, Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention if irritation or symptoms persist.
3. Eye Contact, Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.
4. Skin Contact, May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
5. Ingestion, May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water. Seek medical attention if irritation or symptoms persist.
6. Do not allow product to enter drains. Prevent further spillage if safe.
7. Methods and material for containment and cleaning up: Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
8. Ensure correct PPE is worn, eye/face protection, suitable gloves and clothing.
9. Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers. Store at temperatures above 5 °C.
10. EWC code 10 13 06 Take all empty packaging back to region and dispose of in Drum B

Documents Associated with this Risk Assessment : Tilemaster Super flow 30 powder.pdf(SDS)

Review Date : 23/12/2023