

Designer Contracts Ltd

Risk Assessment

Reference: GENFITLAM

Title	Fitting Laminate – General Risk Assessment	Date Of Assessment	Wed 01 Mar 2023
Site	Designer Contracts Ltd Unit 8	Location	All Sites
Risk Assessor	Laura Cross	Assisted By	Antony Maidens
Non-Employees Involved	-	People At Risk	Employees, Contractors
Task Description	Fitting Laminate		
Review Date	Fri 01 Mar 2024	Reviewer	Laura Cross

Hazards

Hazard	Slips, Trips & Falls
Risk Of Harm	Slips, Trips & Falls
Existing Control Measures	<ol style="list-style-type: none"> 1. Uneven surfaces – The risk of these can be reduced by providing walkways that are clearly designated as walkways, having good conditions underfoot, and being well lit. 2. Obstacles – Instances of slipping and tripping over obstacles can be dramatically reduced by everyone keeping their work and storage areas tidy and designating specific areas for waste collection 3. Wet or slippery surfaces – If a surface is slippery with mud it should be treated with stone, and if it is slippery with ice it should be treated with grit. Any areas that are slippery should be signposted. Ensure you stick to marked walkways when onsite to avoid trips and slips. 4. Trailing cables – Cordless tools should be used where possible. If this is not possible, cables should be run at high levels. 5. Report any unsafe work areas immediately. Ensure the area worked in is left clean and tidy. Observe/Obey any site Health & Safety posters/information/instruction, at all times. In the event of an accident please report to the first aider and report it to the Designer Contracts Office. 6. If using stairs, ensure the area is clear of obstruction and always ask for assistance if required

Hazard	Electrical
Risk Of Harm	Electric Shock
Existing Control Measures	<ol style="list-style-type: none"> 1. Ensure correct tools are used for the job at all times. 2. Use 110v or battery operated tools where possible. 3. Ensure tools are PAT tested annually and in accordance with HSE guidelines (Sub-Contractors have a signed agreement with Designer Contracts). 4. Ask for electricity to be turned off before cutting around any electrical wires (if present)

Hazard	Electric Stapler
Risk Of Harm	Projectiles and Electric Shock
Existing Control Measures	<ol style="list-style-type: none"> 1. Only to be used by trained operator. Use as per User Manual 2. Keep personnel away whilst operating power tools and use of correct signage where applicable. 3. When operating ensure stapler / nailer is in direct contact with the item to be stapled/nailed before commencing activity 4. Do not over reach. Keep proper footing and balance at all times 5. Regular inspection and cleaning should be carried out to ensure the tool is in good working order 6. Disconnect the plug from the power source before making any adjustment, changing accessories or storing power tools. PAT testing to be carried out on appliance. 7. Correct use of required PPE at all times. 8. Only use 8mm & 10mm staples

Hazard	Electrical Saws
Risk Of Harm	Cuts, Lacerations, Electric Shock
Existing Control Measures	<ol style="list-style-type: none"> 1. Do not expose saw to damp conditions, rain or water. 2. Ensure PAT testing has been carried out as required. 3. Regular cleaning and inspection to be carried out to ensure the tool is in good working order 4. Remove any clutter from work areas to ensure a full range of movement and clear of obstructions. 5. Stay alert. Do not use under the influence of medication, drugs or alcohol. 6. Ensure correct PPE is worn at all times to limit exposure to heated air and surfaces, as well as any airborne plastic or debris

Hazard	Hazardous Substances
Risk Of Harm	Serious injury to self and others if not following the COSHH assessment correctly
Existing Control Measures	1. Ensure you have a copy of the relevant COSHH assessment for the product using alongside the laminate

Hazard	Manual handling
Risk Of Harm	Injury to self and others
Existing Control Measures	1. Follow appropriate manual handling techniques at all times – see separate manual handling risk assessment. Ensure 2-man lift where necessary. 2. Ensure safety boots are worn at all times

Hazard	Working Alone
Risk Of Harm	No one may be aware if you are injured
Existing Control Measures	1. If working alone please ensure you maintain hourly contact with Designer Contracts – if you need assistance please call the office immediately. 2. Inform the site manager that you are working alone so that they are aware to check on you 3. Please see separate lone working policy

Hazard	Confined Spaces
Risk Of Harm	Dust generation from cutting product or COSHH products could cause harm to yourself or others
Existing Control Measures	1. Where possible laminate must be cut in a well ventilated area e.g. outdoors.If this is not possible, Fitters are advised that they wear FFP3 masks

Hazard	Knife and Saw
Risk Of Harm	Cuts & Lacerations
Existing Control Measures	<ol style="list-style-type: none"> 1. Ensure operatives hand and body parts are kept clear of moving blade during operation 2. Ensure constant eye contact is made with saw and item being sawn as distractions can cause you to loose control of equipment 3. Condition of blades and knives to be inspected prior to use. 4. Cut away from body and not across or on any body parts. 5. Store in a protective holder or tool box when not in use. 6. Correct use of required PPE at all times

Hazard	Staple Guns
Risk Of Harm	Harm from projectiles
Existing Control Measures	<ol style="list-style-type: none"> 1. Only to be used by trained operator. 2. Use as per User Manual 3. Keep clear of personnel away whilst operating power tools 4. When operating ensure stapler / nailer is in direct contact with the item to be stapled/nailed before commencing activity 5. Ensure PPE is worn – safety googles / glasses, gloves and safety shoes 6. Only use 8mm & 10mm Staples

Hazard	Hammer and Mallet
Risk Of Harm	Strike from hammer
Existing Control Measures	<ol style="list-style-type: none"> 1. Check general state of hammer before use. Attention to be paid to handle condition and grip. Head of hammer is firmly attached to handle. 2. Keep work area well lit and free from debris. 3. Select a hammer that is comfortable to use and is the right size and weight for the task. 4. Be aware of your surroundings and other workers. 5. Use of correct PPE at all times

Hazard	Vacuum Cleaner
Risk Of Harm	Electrical & tripping
Existing Control Measures	<ol style="list-style-type: none">1. Checks to be in place for overall condition of Hoover, cord and attachments2. Ensure PAT test is conforming to current standards.3. Keep the cord length (if applicable) is kept to a minimum to avoid further hazards.4. Ensure the equipment is switched off before plugging in or unplugging from power source