

HAZARDOUS SUBSTANCES RISK ASSESSMENT

Designer Contracts Ltd

Unit 8, Church View, Coney Green, Chesterfield, S45 9HA

CPL Mapei Latexplan Trade Fast (Ex Premium) A	Date of Assessment : 24/05/2023	Reference : CPL Mapei Latexplan Trade Fast (Ex Premium) A
Risk Assessor : Laura Cross	Risk Assessor :	
Other People Involved in Making This Assessment : Antony Maidens		



R or H Descriptors:	S or P Descriptors:
H317 May cause an allergic skin reaction H318 Causes serious eye damage	P261 Avoid breathing dust/fume/gas/mist/vapours/spray P280 Wear protective gloves/protective clothing/eye protection/face protection P310 Immediately call a POISON CENTER or doctor/physician P362 Take off contaminated clothing and wash before reuse P305+351+338 IF IN EYES; Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing P333+313 If skin irritation or a rash occurs Get medical advice/attention P501 Dispose of contents/container to ...xxxxx
Additional Information P501 Dispose of contents/container in accordance with applicable regulations	
Workspace Exposure Limit (WEL) No WEL stated on Safety Data Sheet	

Primary route(s) of entry : Absorption, Ingestion, Inhalation	
This is a Group C Substance.	The quantity used per batch or work period is: Medium (1-1000kg or 1-1000L)
The Substance is a Solid of High dustiness	
Containment is the control measure appropriate to control the health risks from the use of this substance. Health Surveillance is not required.	

Existing Control Measures
1. Always use in well ventilated area.

2. : First aid measures: In case of skin contact: Immediately take off all contaminated clothing. Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.
3. First aid cont..OBTAIN IMMEDIATE MEDICAL ATTENTION. Wash thoroughly the body (shower or bath). Remove contaminated clothing immediately and dispose of safely.
4. First aid :In case of eyes contact: After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Protect uninjured eye
5. In case of Ingestion: Do not induce vomiting, get medical attention showing the SDS and the hazard label. In case of Inhalation: Remove casualty to fresh air and keep warm and at rest.
6. Firefighting measures: Suitable extinguishing media: Water. Carbon dioxide (CO2). Do not inhale explosion and combustion gases. Advice for firefighters Use suitable breathing apparatus
7. Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
8. Methods and material for containment and cleaning up Take up mechanically and dispose of according to local/state/federal regulations Scoop into containers and seal for disposal. Retain contaminated washing water and dispose it.
9. Avoid contact with skin and eyes, inhalation of vapours and mists. Don't use empty container before they have been cleaned. Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
10. Contaminated clothing should be changed before entering eating areas. Do not eat or drink while working.
11. Keep away from food, drink and feed.
12. PPE: Eye protection: Use close fitting safety goggles, don't use eye lens. Protection for skin: Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.
13. PPE:Protection for hands: Suitable materials for safety gloves; EN 374: Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$. Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.
14. PPE: Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$. Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$. Nitrile gloves are suggested (1,3 mm; 480 min). Not recommended gloves: not waterproof gloves
15. Contains cement. Cement gives a strong alkaline reaction with water and body fluids (e.g. sweat and eye fluids), therefore the contact with skin and eyes should be carefully avoided.
16. Adopt good working practices, so that the product is not released into the environment Do not dispose of waste into sewers. Hazardous waste: Yes Do not allow to enter drains or watercourses
17. Waste code 10 12 03 Always return empty packaging to region and dispose of in Drum B

Documents Associated with this Risk Assessment : LATEXPLAN TRADE FAST (EX PREMIUM) A.pdf(SDS) Mapei Latexplan Screed Trade Fast Part A SDS.pdf(safety Data Sheet)

Review Date : 09/06/2024