

HAZARDOUS SUBSTANCES RISK ASSESSMENT

Designer Contracts Ltd

Unit 8, Church View, Coney Green, Chesterfield, S45 9HA

CPL Mapei Latexplan Trade Fast Part B	Date of Assessment : 24/05/2023	Reference : CPL - Mapei Latexplan Trade Fast Part B
Risk Assessor : Laura Cross	Risk Assessor :	
Other People Involved in Making This Assessment : Antony Maidens		

R or H Descriptors:	S or P Descriptors:
Additional Information	
Workspace Exposure Limit (WEL) No WEL stated on Safety Data Sheet	

Primary route(s) of entry : Absorption, Ingestion, Inhalation	
This is a Group Substance.	The quantity used per batch or work period is: Medium (1-1000kg or 1-1000L)
The Substance is a Liquid of Medium volatility	
is the control measure appropriate to control the health risks from the use of this substance. Health Surveillance is not required.	

Existing Control Measures
1. Always use in well ventilated area.
2. : First aid measures: In case of skin contact: Immediately take off all contaminated clothing. Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.
3. Firefighting measures: Suitable extinguishing media: Water. Carbon dioxide (CO2). Do not inhale explosion and combustion gases. Advice for firefighters Use suitable breathing apparatus
4. Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Limit leakages with earth or sand.
5. Methods and material for containment and cleaning up Suitable material for taking up: absorbing material, organic, sand Retain contaminated washing water and dispose it
6. Avoid contact with skin and eyes, inhalation of vapours and mists.
7. Do not eat or drink while working.
8. Keep away from food, drink and feed.
9. PPE: Eye protection: Not needed for normal use. Anyway, operate according good working practices. Protection for skin: No special precaution must be adopted for normal use

10. PPE:Protection for hands: Suitable materials for safety gloves; EN 374: Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$. Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

11. PPE: Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$. Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$. Nitrile gloves are suggested (1,3 mm; 480 min). Not recommended gloves: not waterproof gloves

12. Adopt good working practices, so that the product is not released into the environment

13. Waste treatment methods Recover, if possible. In so doing, comply with the local and national regulations currently in force.

14. Waste code for hardened product 08 04 10. Waste code for not hardened product: 08 04 14. Always return empty packaging to region and dispose of in Drum B

15. The product is not classified as dangerous in the meaning of transport regulations.

Documents Associated with this Risk Assessment : latexplan-trade-part-b-msds.pdf(SDS) CPL - Mapei Latexplan Screed Trade Fast Part B.pdf(Safety Data sheet)

Review Date : 09/06/2024