HAZARDOUS SUBSTANCES RISK ASSESSMENT

Designer Contracts Ltd

Unit 8, Church View, Coney Green, Chesterfield, S45 9HA

CPL - Stopgap 121 Acrylic Primer (Fball)	Date of Assessment : 23/05/2023	Reference : CPL - Stopgap 121 Acrylic Primer (Fball)
Risk Assessor : Laura Cross	Risk Assessor :	
Other People Involved in Making This Assessment : Antony Maidens		

R or H Descriptors:	S or P Descriptors:	
Additional Information		
Workspace Exposure Limit (WEL) No WEL stated on SDS		

Primary route(s) of entry: Absorption, Ingestion, Inhalation	
This is a Group Substance.	The quantity used per batch or work period is: Medium (1-1000kg or 1-1000L)
The Substance is a Liquid of Low volatility	

is the control measure appropriate to control the health risks from the use of this substance. Health Surveillance is not required.

Existing Control Measures

- 1. Always use in a well ventilated area.
- 2. First aid measures: Inhalation Fresh air. Ingestion Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention if any discomfort continues.
- 3. Skin contact Wash skin thoroughly with soap and water. Remove contaminated clothing. Get medical attention if irritation persists after washing. Eye contact Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.
- 4. Firefighting measures: The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire. Special protective equipment for firefighters Wear chemical protective suit.
- 5. Accidental release measures: Do not discharge into drains or watercourses or onto the ground. Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely.
- 6. Wash at the end of each work shift and before eating, smoking and using the toilet.
- 7. Keep away from food, drink and animal feeding stuffs. Store in tightly-closed, original container.
- 8. PPE: Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
- 9. PPE: Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.



- 10. Hygiene measures Provide eyewash station. No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.
- 11. Protect from freezing and direct sunlight.
- 12. Dispose waste to licensed waste disposal site in accordance with the req of the local Waste Disposal Authority. Small quantities be absorbed in sand and allowed to dry, prior to disposal as low haz waste. Lgr quantities disposed of as controlled liquid waste via a licensed waste operator.
- 13. Return all empty containers back to region to be dispose of in Drum B

Documents Associated with this Risk Assessment : Stopgap-P121-iss-8.pdf(SDS)

Review Date: 07/06/2024

