

## HAZARDOUS SUBSTANCES RISK ASSESSMENT

### Designer Contracts Ltd

Unit 8, Church View, Coney Green, Chesterfield, S45 9HA

<b>CPL Flexyfix</b>	<b>Date of Assessment :</b> 10/08/2023	<b>Reference :</b> CPL - Flexyfix
<b>Risk Assessor :</b> Laura Cross	<b>Risk Assessor :</b>	
<b>Other People Involved in Making This Assessment :</b> Antony Maidens		

<b>R or H Descriptors:</b>	<b>S or P Descriptors:</b>
<b>Additional Information</b>	
<b>Workspace Exposure Limit (WEL)</b> No WEL stated on Safety Data Sheet	

<b>Primary route(s) of entry :</b> Absorption, Ingestion, Inhalation	
<b>This is a Group Substance.</b>	<b>The quantity used per batch or work period is: Medium (1-1000kg or 1-1000L)</b>
<b>The Substance is a Liquid of Low volatility</b>	
<b>is the control measure appropriate to control the health risks from the use of this substance. Health Surveillance is not required.</b>	

<b>Existing Control Measures</b>
1. Always use in well ventilated areas.
2. First aid measures: If you feel unwell, seek medical advice. After Inhalation, remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.
3. After skin contact: Rinse with water. Soap may be used. Take victim to a doctor if irritation persists. After eye contact: Rinse with water. Take victim to an ophthalmologist if irritation persists After ingestion: Rinse mouth with water. Consult a doctor/medical service if you feel unwell.
4. Suitable extinguishing media: Adapt extinguishing media to the environment. Unsuitable extinguishing media None. Special exposure hazards Upon combustion: formation of CO, CO2 and small quantities of nitrous vapours, hydrogen chloride.
5. No specific fire fighting instructions required. Special protective equipment for firefighters: Gloves. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus
6. Environmental precautions: Contain leaking substance. Use appropriate containment to avoid environmental contamination..
7. Safe storage requirements: Store in a dry area. Store at room temperature. Meet the legal requirements. Max. storage time: 2 year(s).
8. Observe normal hygiene standards. Keep container tightly closed. Do not eat, drink or smoke during work.
9. Gloves to be worn whilst using product.
10. Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC). 08 04 10 (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants other than those mentioned in 08 04 09). All empty packaging to be returned to region and disposed of in Drum A

**Documents Associated with this Risk Assessment : Flexyfix-SDS-Rev-304.pdf(SDS)**

**Review Date : 02/09/2024**