

## HAZARDOUS SUBSTANCES RISK ASSESSMENT

### Designer Contracts Ltd

Unit 8, Church View, Coney Green, Chesterfield, S45 9HA

<b>CPL Stopgap 1200 Pro (Fball) Part B</b>	Date of Assessment : 05/06/2024	Reference : CPL Stopgap 1200 Pro (Fball) Part B
Risk Assessor : Laura Cross	Risk Assessor :	
Other People Involved in Making This Assessment : Antony Maidens		

<b>R or H Descriptors:</b>	<b>S or P Descriptors:</b>
<b>Additional Information</b>	
<b>Workspace Exposure Limit (WEL)</b> No WEL stated on Safety Data Sheet	

<b>Primary route(s) of entry :</b> Absorption, Ingestion, Inhalation	
<b>This is a Group Substance.</b>	<b>The quantity used per batch or work period is: Medium (1-1000kg or 1-1000L)</b>
<b>The Substance is a Liquid of Low volatility</b>	
<b>is the control measure appropriate to control the health risks from the use of this substance. Health Surveillance is not required.</b>	

<b>Existing Control Measures</b>
1. First aid measures: By inhalation: In case of symptoms, move the person affected into fresh air. By skin contact: In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes to the skin (stinging, redness, rashes, blisters,...),
2. By eye contact: Rinse with water until the product has been eliminated. In case of problems, consult a doctor showing the SDS for the product. By ingestion/aspiration: In case of consumption in large quantities, it is recommended to seek medical assistance.
3. Suitable extinguishing media: Product is non-flammable, with a low risk of fire due to the flammability characteristics of the product in normal conditions of storage, handling and use.
4. In the case of the existence of sustained combustion as a result of improper handling, storage or use any type of extinguishing agent can be used (ABC Powder, water,...) Unsuitable extinguishing media: Non-applicable
5. ACCIDENTAL RELEASE MEASURES For non-emergency personnel: Isolate leaks provided that there is no additional risk for the people performing this task. For emergency responders: Wear protective equipment. Keep unprotected persons away.
6. Environmental precautions: This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.
7. Methods and material for containment and cleaning up: It is recommended: Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents.
8. Technical recommendations on general occupational hygiene Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

- |   |
|---|
| 9. Technical recommendations to prevent environmental risks It is not necessary to take special measures to prevent environmental risks.  |
| 10. Technical measures for storage Minimum Temp.: 5 °C Maximum Temp.: 30 °C Maximum time: 6 Months  |
| 11. General conditions for storage Avoid sources of heat, radiation, static electricity and contact with food.  |
| 12. Respiratory protection The use of protection equipment (FFP3) will be necessary if a mist forms or if the occupational exposure limits are exceeded.  |
| 13. Mandatory Protective gloves against minor risks Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+ A1:2018 |
| 14. Mandatory face protection Panoramic glasses against splash/projections. Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.   |
| 15. It is not possible to assign a specific code, as it depends on the intended use by the user Non dangerous, All empty packaging must be returned to region and disposed of in Drum B Waste code 16 03 03 *   |

<b>Documents Associated with this Risk Assessment</b> : Stopgap-1200-Pro-Liquid-iss-5.pdf(SDS)
<b>Review Date</b> : 09/06/2025